
Chains Pot for ATC (Automatic Tool Changer System)

- This system was developed with the emphasis on high precision and durability for ATC chains used in the ATC equipment of machining centers.
- The pot was developed with special strengthened plastic as the main material, with consideration for the following points:
- 1. Changing dimensions over time.
- 2. Dimensional precision.
- 3. Durability.
- 4. Tool extraction force.




Types

HLP-M (Unit Pot types)

In these types, pots are combined with hollow pins for reduced weight and size.

A special plastic insert is added to the front of the unit pot to improve wear resistance.



| Chain No. | Pitch P | Dimensions (mm) | | | | | | | | | | | | |
|------------|------------|-----------------|----|----|-----|-----|-----|----|--|--|--|--|--|--|
| Chain No. | (mm) | Α | В | D | Н | L | Т | W | | | | | | |
| HLP90-40M | 90 | | | | | | | | | | | | | |
| HLP100-40M | 100 | 44.45 | 55 | 60 | 82 | 89 | 4.0 | 60 | | | | | | |
| HLP125-40M | 125 | | | | | | | | | | | | | |
| HLP115-50M | 115 | | 78 | 82 | | | 6.3 | | | | | | | |
| HLP130-50M | 130 | 69.85 | | | 100 | 140 | | 00 | | | | | | |
| HLP140-50M | 140 | | | | 108 | 148 | | 83 | | | | | | |
| HLP160-50M | 160 | | | | | | | | | | | | | |

Note: 1. We can also manufacture to special dimensions.

Chains for Special Applications


Chains and Pots for ATC (Automatic Tool Changer) Systems

HLP-F type (Plastic Pot type)

Plastic pots are built into the hollow pins of the chain.

Features

- 1. Pots are easy to change.
- 2. Pots are made from special plastic for adequate durability.




| Chain No. | Pitch | Dimensions (mm) | | | | | | | | | | | | |
|------------|-----------|-----------------|----|----|-----|------|-----|----|--|--|--|--|--|--|
| | P (mm) | Α | В | D | н | L | Т | w | | | | | | |
| HLP90-40F | 90 | | | | | | | | | | | | | |
| HLP100-40F | 100 | 44.45 | 55 | 68 | 88 | 105 | 4.0 | 60 | | | | | | |
| HLP125-40F | 120 | | | | | | | | | | | | | |
| HLP130-50F | 130 | | 78 | 92 | | 146 | | | | | | | | |
| HLP140-50F | 140 | 69.85 | | | 120 | 1.44 | 6.3 | 83 | | | | | | |
| HLP160-50F | 160 | | | | | 144 | | | | | | | | |

SAK-F type (Plastic Pot type)

Similar to the structure of the SAW type, with pots built into unitary chains.

Features

- 1. Light and economical, offering stability and rigidity.
- 2. Easy to position the tools.



| Chain No. | | Pitch (mm) | | Dimensions (mm) | | | | | | | | | | |
|------------|--------|----------------|----------------|-----------------|----|-------|-------|-------|------|-----|-------|--|--|--|
| | Р | P ₁ | P ₂ | Α | В | С | D | G | Н | L | w | | | |
| SAK100-40F | 95.25 | 63.5 | 31.75 | 44.45 | 55 | 53.18 | 19.05 | 92.0 | 53.0 | 102 | 19.05 | | | |
| SAK120-50F | 114.30 | 76.2 | 38.10 | 69.85 | 78 | 77.10 | 22.23 | 115.3 | 68.3 | 148 | 25.40 | | | |
| SAK140-50F | 133.35 | 88.9 | 44.45 | 69.85 | 78 | 73.60 | 25.4 | 136.0 | 80.0 | 148 | 25.40 | | | |


Chains and Pots for ATC (Automatic Tool Changer) Systems

SAW-F type (Plastic Pot type)

Plastic pots are built into a chain that splits between left and right sides.

Features

- 1. Lightweight and economical.
- 2. Easy to position the tools.




| Chain No. | | Pitch (mm) | | Dimensions (mm) | | | | | | | | | | |
|------------|--------|----------------|----------------|-----------------|----|------|-------|-------|------|-----|------|--|--|--|
| | P | P ₁ | P ₂ | Α | В | С | D | G | Н | L | w | | | |
| SAW120-50F | 114.30 | 76.2 | 38.10 | 69.85 | 78 | 52.6 | 22.23 | 115.3 | 68.3 | 155 | 25.4 | | | |
| SAW120-50F | 114.30 | 76.2 | 38.10 | 69.85 | 78 | 77.1 | 22.23 | 136.0 | 80.0 | 148 | 25.4 | | | |
| SAW140-50F | 133.35 | 88.9 | 44.45 | 69.85 | 78 | 73.6 | 25.40 | 136.0 | 80.0 | 148 | 25.4 | | | |


K2S-F type (Plastic Pot type)

This type has a chain attachment with a pot tipping function, so that it can be used in upright machining centers.

Features

- 1. The tool changing system can be simplified.
- 2. The chain has side rollers, so the tools are prevented from tilting or swaying.





| Ohaira Na | Pitch | (mm) | Dimensions (mm) | | | | | | | | | | | | | |
|-------------|-------|----------------|-----------------|-----|-------|------|----|-------|------|-------|-----|-----|-------|----|-------|-------|
| Chain No. | Р | P ₁ | Α | С | D | E | F | G | Н | - 1 | L | М | N | R | S | W |
| K2S2080-40F | 101.6 | 50.8 | 44.45 | 70 | 15.88 | 43.5 | 15 | 78.5 | 58.5 | 92.6 | 140 | 105 | 60.00 | 28 | 19.05 | 15.88 |
| K2S2100-50F | 127.0 | 63.5 | 69.85 | 117 | 19.05 | 70.0 | 20 | 120.0 | 90.0 | 143.0 | 200 | 150 | 91.25 | 28 | 22.22 | 19.40 |